


Tag No.		
Flow	OPER	
	MAX	
Temp.	OPER.	
	MAX	150 °C
Press.	OPER.	
	MAX	10Bar
Fluid		N2
Pipe Size		40A
Connection		JIS 10K RF
Accuracy		±0.5 FS
Output		4-20mA, Pulse RS-485
POWER		24VDC
ENCLOSURE		IP 67
Q'ty		3 set

7	FLOW BODY & FLANGE	SUS 304	
6	SENSING PROTECTION	SUS 304	-
5	HEATER	Ceramic+SUS303	-
4	RTD	Ceramic+SUS303	-
3	NIPPLE	SUS 316	3/4"(PT)
2	COMPRESSION FITTING	SUS 316	3/4"(PT)
1	HEAD	AL.C	
NO.	DESCRIPTION	MAT'L	REMARK

 <b>Golden Rules Co.,Ltd</b>		SCALE N/S	UNIT mm	REV. A
<b>TITLE</b> <b>THERMAL MASS FLOW METER</b> <b>(KC-2610GI) Insertion &amp; Integral Type</b>		PROJECT		
		DRAWING NO. KC-2610-07-2		
DESIGNED BY Y.J. Lee	CHECKED BY H.M. Hong	APPROVED BY H.M. Hong	DATE 2018.07.10	SHEET NO. 1/1