



Tag No.		
Flow	MAX	8,121Nm ³ /h
	MIN	1 Nm ³ /h
Temp.	OPER.	40°C
	MAX	50 °C
Press.	OPER.	0.4Kgf/cm ²
	MAX	0.6Kgf/cm ²
Fluid	Air	
Pipe Size	200A	
Mounting	PT 1"(33.4mm)	
Accuracy	±0.5 FS	
Output	4-20mA, 4 wire	
POWER	24VDC	
ENCLOSURE	IP 67	
Q'ty	10 sets	

NO.	DESCRIPTION	MAT'L	REMARK
8	BALL VALVE	SUS304	1"(PT)
7	FLANGE	SUS304	1"
6	SENSING PROTECTION	SUS 303	-
5	HEATER	Ceramic+SUS303	-
4	RTD	Ceramic+SUS303	-
3	NIPPLE	SUS 304	1"(PT)
2	COMPRESSION FITTING	SUS 316	3/4"(PT)
1	HEAD	AL.C	

NO	DATE	REVISION	REV'D BY	CHK'D BY	Gloden Rules Co.,Ltd	SCALE	UNIT	REV.
△	.	.				N/S	mm	△
△	.	.						
△	.	.						
△	.	.						
△	.	.						

TITLE	PROJECT	DRAWING NO.	DATE
THERMAL MASS FLOW METER (KC-2610GI) Insertion & Integral Type		KC-2610GI	2015.05.13
DESIGNED BY	CHECKED BY	APPROVED BY	SHEET NO.
			1/1